

Segatrici a nastro verticali per il taglio del legno
 Senkrechte Bandsägen zum Holzschnitt
 Scieuses à ruban verticales de débitage du bois

SERIE E - EXPORT



Mod. E 440
Mod. E 520
Mod. E 620
Mod. E 720

Versioni elettriche
Electric versions
Electric Version

Di serie - Seriell - De série
 Switch di sicurezza
 Sicherheitsschalter
 Interrupteur de sécurité



Di serie - Seriell - De série
 Due guida lama di precisione in ottone
 Präzisionsmesserführung Messing - Deux guide
 lame de précision laiton



Dimensioni - Size
 Dimension - Größe
 CM.

Mod.	a	b	c	d	e	f	g	i	R	Ø	Ø volani
E 440	43	29	60	60	91	182	56	85	20	440	mm
E 520	50	39	68	78	91	202	62	100	20	520	mm
E 620	61	43	80	97	92	217	83	120	20	620	mm
E 720	70	49	80	97	93	237	85	125	25	720	mm

Livello di potenza acustica LWA 93,3 dB

DATI TECNICI

Cod.	Mod.Ø	Funzionamento - Operation - Arbeitsweise - Opération	Kg.
SN4T	E 440	Trifase - Three-phase - Dreiphasen - Triphasé 400V KW 2,2	150
SN4M	E 440	Monofase - Single-phase - Einphasen - Monophasé 230V KW 2,2	150
SN5T	E 520	Trifase - Three-phase - Dreiphasen - Triphasé 400V KW 2,2	200
SN5M	E 520	Monofase - Single-phase - Einphasen - Monophasé 230V KW 2,2	200
SN6T	E 620	Trifase - Three-phase - Dreiphasen - Triphasé 400V KW 2,2	260
SN6M	E 620	Monofase - Single-phase - Einphasen - Monophasé 230V KW 2,2	260
SN7T	E 720	Trifase - Three-phase - Dreiphasen - Triphasé 400V KW3	320

LAME DI RICAMBIO

Cod.	Serie	Descrizione - Description - Beschreibung
94	E 440	Lama - Blade - Messer - Lame - "Carbonio" mm. 3830 25x0,5 d8
93	E 520	Lama - Blade - Messer - Lame - "Carbonio" mm. 4300 30x0,6 d10
92	E 620	Lama - Blade - Messer - Lame - "Carbonio" mm. 4740 32x0,7 d12
91	E 720	Lama - Blade - Messer - Lame - "Carbonio" mm. 5200 35x0,9 d12